
Prof. Dr.-Ing. Stefan Deßloch AG Heterogene Informationssysteme Geb. 36, Raum 329 Tel. 0631/205 3275 dessloch@informatik.uni-kl.de



Chapter 1 – Motivation





Middleware

- Middleware
 - supports the development, deployment, and execution of complex information systems
 - facilitates interaction between and integration of applications across multiple distributed, heterogeneous platforms and data sources
- Two major aspects
 - middleware as a programming abstraction
 - middleware as infrastructure
- Principles
 - make distribution transparent
 - support standardized APIs/languages/data formats to overcome platform heterogeneity
 - application logic independent from infrastructure code
 - powerful programming abstractions



3

Middleware for Information Systems

application

driver manager

DB2

driver

Oracle

driver

Database Gateways

- Uniform Database Access
 - query language (SQL)
 - meta data
 - programming interface
- Dynamic, late binding to specific DB/DBS
 - call level interface (CLI)
 - no vendor-specific pre-compiler
 - dynamic binding of run-time libraries
 - late query compilation
- Simultaneous access to multiple DB/DBMS
 - architecture supports use of (multiple) DBMS-specific drivers
 - coordinated by a driver manager
- Support for vendor-specific extensions



4

Middleware for Information Systems

O/JDBC API


© Prof. Dr.-Ing. S. Deßloch


Communication and Distributed Processing

- Distributed (Information) System
 - consists of (possibly autonomous) subsystems
 - jointly working in a coordinated manner
- How do subsystems communicate?
 - Remote Procedure Calls (RPC)
 - transparently invoke procedures located on other machines
 - Peer-To-Peer-Messaging
 - Message Queuing
- Transactional Support (ACID properties) for distributed processing
 - Server/system components are Resource Managers
 - (Transactional) Remote Procedure Calls (TRPC)
 - Distributed Transaction Processing



5






Application Middleware - Main Tasks


- Distributed computing infrastructure (RPC, RMI)
- Transactional capabilities
 - programming abstractions (demarcation)
 - distributed transaction management
- Security services
 - authentication, authorization, secure transmission, ...
- Unified access to heterogeneous information sources and application systems
- Scalable and efficient application processing
 - large number of client applications or end users
- Reliability, high availability


Programming model abstractions that allow the developer to focus on application logic (i.e., ignore infrastructure as much as possible)




8










Web Services

- New distributed computing platform built on existing infrastructure including XML & HTTP
 - Web services are for B2B what browsers are for B2C
- Self-contained, self describing, modular service that can be published, located and invoked across the web
 - Refer to open standards and specifications:
 - component model (WSDL)
 - inter-component model communication (SOAP)
 - discovery (UDDI)
 - Platform- and implementation-independent access
 - Described, searched, and executed based on XML
- Enable component-oriented applications
 - Loose coupling from client to service
 - Enable to integrate legacy systems into the web
 - Useful for other distributed computing frameworks such as Corba, DCOM, EJBs



13



Service-Oriented Architecture (SOA) Service Requestor Finds required services via Service Broker Binds to services via Service Provider Service Service Provider Provider Provides e-business services Publish Publishes availability of these services through a registry Service Service Service Registry Registry Requestor Provides support for publishing and locating services Like telephone yellow pages 15 Middleware for Information Systems

Standards

- UDDI
 - Universal Description, Discovery and Integration
 - Registry of and search for web services
- SOAP
 - Simple Object Access Protocol
 - Communication protocol
- WSDL
 - Web Services Description Language
 - Description of a service's functionality
- XML
 - eXtensible Markup Language
 - Underlying basic representation approach




16

Role of the WWW for IS

- Initial purpose: sharing information on the internet
 - technologies
 - HTML documents
 - HTTP protocol
 - web browser as client for internet information access
- For Information Systems: connecting remote clients with applications across the internet/intranet
 - "web-enabled" applications
 - extend application reach to the consumer
 - leverage advantages of web technologies
 - web browser as a universal application client
 - "thin client"
 - no application-specific client code has to be installed
 - requirements
 - content is coming from dynamic sources (IS, DBS)
 - request to access a resource has to result in application invocation
 - session state: tracking repeated interactions of the same client with a web server



17



Outlook on EIS

- Data/Information Integration
 - integrated access to (heterogeneous) data originating from multiple sources
 queries range over date from multiple DBs!
 - virtual integration: integrate on access/query (e.g., federated DBMS)
 - materialized integration: extract, transform, load data into a single materialized data warehouse in advance (e.g., data replication, data warehousing)
 - needs a strong foundation to overcome multiple kinds of heterogeneity
- Enterprise Application Integration
 - integration of (heterogeneous, coarse-grained) applications within an enterprise (vs. development of new application)
 - integration across different middleware platforms
- Business-to-business Integration
 - support interactions, integration of business processes among trading partners, across company boundaries
 - foundation for e-business, e-commerce



19